
# PROGRADINO (SERIES C)

Anodized Aluminum


KALLOS PROGRADINO (KCSN) is a contemporary design ALUMINUM Step edge profile with a unique serrated grip edge. Providing edge protection to the floor covering and highlighting the step edge.

KALLOS Aluminum Profiles are supplied with protection film for added protection, before, during and after application - as standard.





### **Profile Data**




ARTICLE	W( mm )	H ( mm )	L(mm)	
KCSNSR-53-33-XX	53	33	3.30	
KCSNDR-70-33-XX	70	33	3.30	

» When ordering specify the color of Aluminum profile for example: KCNSR-53-33-XX the XX stand as the profile color which can be selected from the color chart below.



### Laying instructions



- Ensure the steps are dry, clean, free of debris, level and even.
- If Predrilled use the drill holes to mark steps for drilling location.
- 3 Drill and Plug the steps.
- 4 Apply suitable adhesive to the underside of the nosing and apply nosing to the step.
- **5** Screw down the step with the appropriate size screws.



MS Matt Silver



**GT** Matt Brown



MC Matt Black



MG-Matt Gold

### **Technical Data**

## Aluminium AA 6063T6 / UNS A96063

Anodished to DIN 17611				
	Si %	0.2 - 0.6		
	Fe %	0.35		
	Cu %	0.1		
y	Mn %	0.1		
	Mg %	0.45 - 0.9		
	Zn %	0.1		
	Ti %	0.1		
	Cr %	0.1		
	Al	Balance		

# General Cleaning and Maintenance

- » Inserts:
- All inserts should be cleaned using a neutral detergent and thoroughly rinsed with clean water. Ensure all inserts are dry prior to receiving foot traffic.
- » Aluminium Channel:

These can be polished using steel wool or cloth to maintain the appearance - under no circumstances should solvent cleaners be utilised in cleaning or maintaining Aluminium Products.



<sup>6</sup> Apply insert (if separate) or insert pip to cover the screw head.

<sup>\*</sup> Size can be customized, Production upon request, timing and price to be agreed